

Page 1 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 16.01.2014 / 0001
Replaces revision of / Version: 16.01.2014 / 0001
Valid from: 16.01.2014
PDF print date: 09.05.2014
Oil for pneumatic tools 1 L Art.: 128863

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Oil for pneumatic tools 1 L
Art.: 128863

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Hydraulic oil
Lubricating oil

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Berner Produkten b.v., Vogelzankweg 175, NL-6374 AC Landgraaf
Telephone: +31 45 53 39 133, Fax: +31 45 53 14 588
info@berner.nl www.berner.nl

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

Page 2 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 16.01.2014 / 0001
 Replaces revision of / Version: 16.01.2014 / 0001
 Valid from: 16.01.2014
 PDF print date: 09.05.2014
 Oil for pneumatic tools 1 L Art.: 128863

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

The mixture is not classified as dangerous in the terms of the directive 1999/45/EC.

2.2 Label elements

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

Not applicable

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

Product can compose a film on the water surface, which can prevent oxygen exchange.

Hazardous to drinking water, on escape of even small quantities.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

--	
Registration number (REACH)	--
Index	-
EINECS, ELINCS, NLP	-
CAS	-
content %	
Classification according to Directive 67/548/EEC	---
Classification according to Regulation (EC) 1272/2008 (CLP)	---

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Unsuitable cleaning product:

Solvent

Thinners

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Page 3 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 16.01.2014 / 0001

Replaces revision of / Version: 16.01.2014 / 0001

Valid from: 16.01.2014

PDF print date: 09.05.2014

Oil for pneumatic tools 1 L Art.: 128863

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

With long-term contact:

Drying of the skin.

Dermatitis (skin inflammation)

Oil acne

On vapour formation:

Irritation of the respiratory tract

Ingestion:

Gastrointestinal disturbances

Nausea

Vomiting

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Extinction powder

Sand

Unsuitable extinguishing media

Water

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of phosphorus

Toxic pyrolysis products.

Flammable vapour/air mixtures

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Page 4 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 16.01.2014 / 0001

Replaces revision of / Version: 16.01.2014 / 0001

Valid from: 16.01.2014

PDF print date: 09.05.2014

Oil for pneumatic tools 1 L Art.: 128863

Avoid formation of oil mist.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Oil binder

Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid formation of oil mist.

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Do not heat to temperatures close to flash point.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Use resistant floors, if necessary designed as collection pan.

Protect against moisture and store closed.

Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ⓢ

Page 5 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 16.01.2014 / 0001
 Replaces revision of / Version: 16.01.2014 / 0001
 Valid from: 16.01.2014
 PDF print date: 09.05.2014
 Oil for pneumatic tools 1 L Art.: 128863

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	---
BMGV: ---	Other information: ---	

Ⓢ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection:

Protective gloves, oil resistant (EN 374)

If applicable

Protective Neoprene® / polychloroprene gloves (EN 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

>240

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

> 240

Protective hand cream recommended.

The recommended maximum wearing time is 50% of breakthrough time.

The breakthrough times determined in accordance with EN 374 Part III were not obtained under practical conditions.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:

Page 6 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 16.01.2014 / 0001

Replaces revision of / Version: 16.01.2014 / 0001

Valid from: 16.01.2014

PDF print date: 09.05.2014

Oil for pneumatic tools 1 L Art.: 128863

Normally not necessary.

With oil mist formation:

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Light yellow
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	200 °C (ISO 2592 (Cleveland, open cup))
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,86 g/cm ³ (15°C, DIN 51757)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not miscible
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	32 mm ² /s (DIN 51562 (Ubbelohde viscometer))
Explosive properties:	Product is not explosive.
Oxidising properties:	No

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 16.01.2014 / 0001

Replaces revision of / Version: 16.01.2014 / 0001

Valid from: 16.01.2014

PDF print date: 09.05.2014

Oil for pneumatic tools 1 L Art.: 128863

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.2 to 10.6.

The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6.

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

Oil for pneumatic tools 1 L

Art.: 128863

Toxicity/effect	Endp oint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.

GB

Page 8 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 16.01.2014 / 0001
 Replaces revision of / Version: 16.01.2014 / 0001
 Valid from: 16.01.2014
 PDF print date: 09.05.2014
 Oil for pneumatic tools 1 L Art.: 128863

Reproductive toxicity:							n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):							n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):							n.d.a.
Aspiration hazard:							n.d.a.
Respiratory tract irritation:							n.d.a.
Repeated dose toxicity:							n.d.a.
Symptoms:							n.d.a.
Other information:							Classification according to calculation procedure.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Oil for pneumatic tools 1 L Art.: 128863

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							Isolate as much as possible with an oil separator.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

Page 9 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 16.01.2014 / 0001

Replaces revision of / Version: 16.01.2014 / 0001

Valid from: 16.01.2014

PDF print date: 09.05.2014

Oil for pneumatic tools 1 L Art.: 128863

13 01 10 mineral based non-chlorinated hydraulic oils

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Pay attention to local and national official regulations

Observe regulations for disposal of old oil/waste.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 10 packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

General statements

UN number: n.a.

Transport by road/by rail (ADR/RID)

UN proper shipping name:

Transport hazard class(es): n.a.

Packing group: n.a.

Classification code: n.a.

LQ (ADR 2013): n.a.

LQ (ADR 2009): n.a.

Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name:

Transport hazard class(es): n.a.

Packing group: n.a.

Marine Pollutant: n.a.

Environmental hazards: Not applicable

Transport by air (IATA)

UN proper shipping name:

Transport hazard class(es): n.a.

Packing group: n.a.

Environmental hazards: Not applicable

Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions: n.a.

VOC (1999/13/EC): n.a.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 16.01.2014 / 0001

Replaces revision of / Version: 16.01.2014 / 0001

Valid from: 16.01.2014

PDF print date: 09.05.2014

Oil for pneumatic tools 1 L Art.: 128863

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

These details refer to the product as it is delivered.

Revised sections:

2

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

Albert Berner
Deutschland GmbH
Bernerstrasse 4
D - 74653 Künzelsau
Tel +49 79 40 12 10
Fax +49 79 40 12 13 00
info@berner.de
www.berner.de

Berner Gesellschaft
m.b.H.
Industriezeile 36
A - 5280 Braunau / Inn
Tel +43 77 22 800 508
Fax +43 77 22 800 184
berner@berner.co.at
www.berner.co.at

Berner Belgien NV/SA
Bernerstraat 1
B - 3620 Lanaken
Tel +31 45 533 93
133(8.00h-16.00h)
Tel +31 6 290 27 464
(16.00h-8.00h)
Fax +31 455 33 92 43
info@berner.be
www.berner.be

Montagetchnik Berner
AG
Kägenstraße 8
CH - 4153 Reinach / Bl. 1
Tel +41 61 71 59 222
Fax +41 61 71 59 333
berner-ag@berner-ag.ch
www.berner-ag.ch

Berner A/S
Stenholm 2
DK - 9400 Nørresundby
Tel +45 99 36 15 00
Fax +45 98 19 24 14
info@berner.dk
www.berner.dk

Berner Montaje y
Fijación, S.L.
P.I. "La Rosa VI"
C/Albert Berner, 2
E - 18330 Chauchina-
Granada-España
Tel +34 90 21 03 504
Fax +34 90 21 13 190
berner-spain@berner.es
www.berner.es

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 16.01.2014 / 0001

Replaces revision of / Version: 16.01.2014 / 0001

Valid from: 16.01.2014

PDF print date: 09.05.2014

Oil for pneumatic tools 1 L Art.: 128863

Berner Kft.
Táblás u. 34
H - 1097 Budapest
Tel +36 (1) 347 1059
Fax +36 (1) 347 1045
info@berner.hu
www.berner.hu

Frimann-Berner AS
Holmaveien 25
N - 1339 Vøyenenga
Tel +47 66 76 55 80
Fax +47 66 76 55 81
info@berner.no
www.berner.no

Berner Succ. Luxembourg
105, Rue des Bruyères
L - 1274 Howald
Tel +31 45 533 93 133
(8.00h-16.00h)
Tel +31 6 290 27 464
(16.00h-8.00h)
Fax +31 455 33 92 43
info@berner.lu
www.berner.lu

Berner spol. s r.o.
Jinonická 80
CZ - 158 00 Praha 5
Tel +420 225 390 666
Fax +420 225 390 660
berner@berner.cz
www.berner.cz

Berner,S.A.
Av. Amália Rodrigues,3510
Manique de Baixo
P - 2785-738 São Domingos
de Rana
Tel ++351 21 448 90 60
Fax ++351 21 448 90 69
marketing.pt@berner.pt
www.berner.pt

Berner Polska Sp. Z.o.o.
Al. Gen. T. Bora-
Komorowskiego 25a
PL - 31-476 Kraków
Tel +48 12 297 62 40
Fax +48 12 297 62 02
office@berner.pl
www.berner.pl

Albert Berner UAB
Kalvarijø 29B, LT09313,
Vilnius, Lithuania
Tel +370-52104355
Fax +370-52350020
info@berner.lt

Berner SK
Berner s r.o.
Jesenského 1
SK - 962 12 Detva
Tel (+421) 45 5410 245
Fax (+421) 45 5410 255
berner@berner.sk
www.berner.sk

Albert Berner
Montageteknik AB
Kumla Gårdsväg 18
S - 14563 Norsborg
Tel +46 85 78 77 800
Fax +46 85 78 77 805
info@berner.se
www.berner.se

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 16.01.2014 / 0001

Replaces revision of / Version: 16.01.2014 / 0001

Valid from: 16.01.2014

PDF print date: 09.05.2014

Oil for pneumatic tools 1 L Art.: 128863

Berner Pultti Oy
Volttikatu 6
FI - 70700 Kuopio
Tel +358-207-590 220
Fax +358-207-590 221
kuopio@berner-
pultti.com

Mitras d.o.o
Brdnikova ulica 34e
SL-1000 Ljubljana
Tel +386-1-256-62-46
Fax +386-1-256-62-45
mitras@siol.com

BERNER d.o.o
CPM Savica Čanci
Trgovačka 2
HR - 10000 Zagreb
Tel +38512 499 470
Fax +38512 499 480
e-mail: safetydata-

Berner Endüstriyel Ürünler
Sanayi ve Ticaret A.Ş.
Ferhatpaşa Mah. G 7 Sok.
31/2
TR - 34858 Kartal-
Sarıyer / İSTANBUL
Tel +90 (0) 216-4713077
Fax +90 (0) 216-4719625
info@berner.com.tr
www.berner.com.tr

Berner S.p.A.
Via dell 'Elettronica 15
I - 37139 Verona
Tel +39 04 58 67 01 11
Fax +39 04 58 67 01 34
info@berner.it
www.berner.it

Albert Berner srl
Str. Vrancei Nr. 51 - 55
RO - 310315 Arad
Tel +40 257 212291
Fax +40 257 250460
office@berner-romania.ro
www.berner-romania.ro

Berner Produkten b.v.
Vogelzankweg 175
NL - 6374 AC Landgraaf
+31 45 53 39 133 (8.00h-
16.00h)
+31 6 290 27 464 (16.00h-
8.00h)
info@berner.nl
www.berner.nl

Berner s.a.r.l.
ZI Les Manteaux
F - 89331 Saint-Julien-du-
Sault Cedex
Tel +33 38 69 94 400
Fax +33 38 69 94 444
contact@berner.fr
www.berner.fr

Albert Berner SIA
Liliju 20, Marupe, Mārupes
novads,
LV-2167, Latvija
Tel +37167840007
Fax +371678440008
info@berner.lv

(c) COPYRIGHT 1987 -
2050 ALL RIGHTS
RESERVED

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
ACGIH American Conference of Governmental Industrial Hygienists
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOEL Acceptable Operator Exposure Level
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
BMGV Biological monitoring guidance value (EH40, UK)
BOD Biochemical oxygen demand
BSEF Bromine Science and Environmental Forum
bw body weight
CAS Chemical Abstracts Service
CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC Collaborative International Pesticides Analytical Council
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
COD Chemical oxygen demand
CTFA Cosmetic, Toiletry, and Fragrance Association
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
DT50 Dwell Time - 50% reduction of start concentration
DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ERC Environmental Release Categories
ES Exposure scenario
etc. et cetera
EU European Union
EWC European Waste Catalogue
Fax. Fax number
gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
HET-CAM Hen's Egg Test - Chorionallantoic Membrane
HGWP Halocarbon Global Warming Potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC Intermediate Bulk Container
IBC (Code) International Bulk Chemical (Code)
IC Inhibitory concentration
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
LC lethal concentration
LC50 lethal concentration 50 percent kill
LCLo lowest published lethal concentration
LD Lethal Dose of a chemical
LD50 Lethal Dose, 50% kill
LDLo Lethal Dose Low
LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAEC No Observed Adverse Effective Concentration
NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship

Page 15 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 16.01.2014 / 0001

Replaces revision of / Version: 16.01.2014 / 0001

Valid from: 16.01.2014

PDF print date: 09.05.2014

Oil for pneumatic tools 1 L Art.: 128863

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.